



## Declaration of Performance

### arcon sunbelt D40 blue HT



#### Coated glass, intended to be used in buildings and construction works

**arcon**  
 Flach- und Sicherheitsglas GmbH & Co. KG  
 Werk Feuchtwangen  
 Industriestraße 10  
 D - 91555 Feuchtwangen

**arcon**  
 Flach- und Sicherheitsglas GmbH & Co. KG  
 Werk Bucha  
 Gewerbegebiet "Am Amselberg" Schorba 4  
 D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2004

Essential characteristics	LE/DoP-Nr.	1008904/CPR/ 2013-07-01	1008905/CPR/ 2013-07-01	1008906/CPR/ 2013-07-01	1008908/CPR/ 2013-07-01	1008910/CPR/ 2013-07-01	1008912/CPR/ 2013-07-01
	AVCP Systems	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	A1	A1	A1	A1	A1	A1
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	40	40	40	40	40	40
Wind, snow, permanent and imposed load resistance (mm)	4	4	5	6	8	10	12
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	30 (-2, -4)	30 (-1, -2)	31 (-1, -3)	32 (-1, -2)	34 (-2, -3)	35 (-2, -3)
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ coated side	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	NPD	NPD	NPD	NPD	NPD	NPD
Light reflection coated/uncoated side $\rho_v, \rho_v'$	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	NPD	NPD	NPD	NPD	NPD	NPD
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	NPD	NPD	NPD	NPD	NPD	NPD
Solar factor	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
 This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2023-04-01	



## Declaration of Performance

### arcon sunbelt D40 oHT



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

Essential characteristics	LE/DoP-Nr.	10052004/CPR/ 2013-07-01	10052005/CPR/ 2013-07-01	10052006/CPR/ 2013-07-01	10052008/CPR/ 2013-07-01	10052010/CPR/ 2013-07-01	10052012/CPR/ 2013-07-01
	AVCP Systems	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	A1	A1	A1	A1	A1	A1
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	40	40	40	40	40	40
Wind, snow, permanent and imposed load resistance (mm)	4	4	5	6	8	10	12
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	30 (-2, -4)	30 (-1, -2)	31 (-1, -3)	32 (-1, -2)	34 (-2, -3)	35 (-2, -3)
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ coated side		0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	44	44	44	44	43	43
Light reflection coated/uncoated side $\rho_v, \rho_v'$		9 / 35	9 / 34	9 / 34	9 / 34	9 / 33	9 / 33
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	29	29	28	28	28	27
Solar reflection coated/uncoated side $\rho_e, \rho_e'$		28 / 40	28 / 39	28 / 38	28 / 36	28 / 34	28 / 33
Solar factor		NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D40 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)

#### EN 1096-4:2018

Essential characteristics	LE/DoP-Nr.	40020100/CPR/ 2013-07-01	40020101/CPR/ 2013-07-01	40020110/CPR/ 2013-07-01	40020111/CPR/ 2013-07-01	40020120/CPR/ 2013-07-01	40020121/CPR/ 2013-07-01
	AVCP Systems	33.1	33.2	44.1	44.2	55.1	55.2
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	NPD	NPD	NPD	NPD	NPD	NPD
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD	NPD	NPD	NPD	NPD
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Thermal properties</b>							
U-value (W/m <sup>2</sup> K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ , coated side		0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	44	44	44	43	43	43
Light reflection coated/uncoated side $\rho_v, \rho_v'$		9 / 34	9 / 34	9 / 34	9 / 34	9 / 33	9 / 33
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	28	27	27	27	27	26
Solar reflection coated/uncoated side $\rho_e, \rho_e'$		28 / 35	28 / 34	28 / 34	28 / 33	28 / 32	28 / 31
Solar factor		NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D40 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
 Flachglas-Veredlung GmbH & Co. KG  
 Werk Feuchtwangen  
 Industriestraße 10  
 D - 91555 Feuchtwangen

**arcon**  
 Flachglas-Veredlung GmbH & Co. KG  
 Werk Bucha  
 Gewerbegebiet "Am Amselberg" Schorba 4  
 D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

	LE/DoP-Nr.	40020130/CPR/ 2013-07-01	40020131/CPR/ 2013-07-01			
<b>Essential characteristics</b>	<b>AVCP Systems</b>	<b>66.1</b>	<b>66.2</b>			
<b>Safety in case of fire</b>						
Resistance to fire	1	NPD	NPD			
Reaction to fire	3.4	NPD	NPD			
External fire performance	3.4	NPD	NPD			
<b>Safety in use</b>						
Bullet resistance	1	NPD	NPD			
Explosion resistance	1	NPD	NPD			
Burglar resistance	3	NPD	NPD			
Pendulum body impact resistance	3	NPD	NPD			
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD			
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD			
<b>Protection against noise</b>						
Direct airborne sound reduction (db)	3	NPD	NPD			
<b>Thermal properties</b>						
U-value (W/m²K)	3	NPD	NPD			
Declared normal emissivity $\epsilon_n$ coated side		0.03	0.03			
<b>Radiation properties</b>						
Light transmission: $\tau_v$	3	43	43			
Light reflection coated/uncoated side $\rho_v, \rho_v'$		9 / 33	9 / 33			
<b>Solar energy characteristics</b>						
Solar transmission $\tau_e$		26	26			
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	28 / 31	28 / 30			
Solar factor		NPD	NPD			
<b>Durability</b>	3	PASS	PASS			

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
 This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D50 oHT



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

Essential characteristics	LE/DoP-Nr.	10048004/CPR/ 2013-07-01	10048005/CPR/ 2013-07-01	10048006/CPR/ 2013-07-01	10048008/CPR/ 2013-07-01	10048010/CPR/ 2013-07-01	10048012/CPR/ 2013-07-01
	AVCP Systems	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	A1	A1	A1	A1	A1	A1
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	40	40	40	40	40	40
Wind, snow, permanent and imposed load resistance (mm)	4	4	5	6	8	10	12
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	30 (-2, -4)	30 (-1, -2)	31 (-1, -3)	32 (-1, -2)	34 (-2, -3)	35 (-2, -3)
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ coated side	3	0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	55	55	55	54	54	53
Light reflection coated/uncoated side $\rho_v, \rho_v'$	3	15 / 28	15 / 28	15 / 27	15 / 27	15 / 27	15 / 26
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	35	34	34	33	32	32
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	38 / 40	38 / 39	38 / 37	38 / 35	38 / 33	38 / 32
Solar factor	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D50 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

Essential characteristics	LE/DoP-Nr.	41048100/CPR/ 2013-07-01	41048101/CPR/ 2013-07-01	41048110/CPR/ 2013-07-01	41048111/CPR/ 2013-07-01	41048120/CPR/ 2013-07-01	41048121/CPR/ 2013-07-01
	AVCP Systems	33.1	33.2	44.1	44.2	55.1	55.2
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	NPD	NPD	NPD	NPD	NPD	NPD
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD	NPD	NPD	NPD	NPD
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ , coated side		0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	54	54	54	54	54	54
Light reflection coated/uncoated side $\rho_v, \rho_v'$		15 / 27	15 / 27	15 / 27	15 / 27	15 / 27	15 / 27
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	32	32	32	32	31	31
Solar reflection coated/uncoated side $\rho_e, \rho_e'$		38 / 34	38 / 33	38 / 33	38 / 32	38 / 31	38 / 30
Solar factor		NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D50 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

	LE/DoP-Nr.	41048130/CPR/ 2013-07-01	41048131/CPR/ 2013-07-01			
<b>Essential characteristics</b>	<b>AVCP Systems</b>	<b>66.1</b>	<b>66.2</b>			
<b>Safety in case of fire</b>						
Resistance to fire	1	NPD	NPD			
Reaction to fire	3.4	NPD	NPD			
External fire performance	3.4	NPD	NPD			
<b>Safety in use</b>						
Bullet resistance	1	NPD	NPD			
Explosion resistance	1	NPD	NPD			
Burglar resistance	3	NPD	NPD			
Pendulum body impact resistance	3	NPD	NPD			
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD			
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD			
<b>Protection against noise</b>						
Direct airborne sound reduction (db)	3	NPD	NPD			
<b>Thermal properties</b>						
U-value (W/m²K)	3	NPD	NPD			
Declared normal emissivity $\epsilon_n$ coated side		0.03	0.03			
<b>Radiation properties</b>						
Light transmission: $\tau_v$	3	53	53			
Light reflection coated/uncoated side $\rho_v, \rho_v'$		15 / 26	15 / 26			
<b>Solar energy characteristics</b>						
Solar transmission $\tau_e$		31	31			
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	38 / 29	38 / 29			
Solar factor		NPD	NPD			
<b>Durability</b>	3	PASS	PASS			

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D60 oHT



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

Essential characteristics	LE/DoP-Nr.	10054004/CPR/ 2013-07-01	10054005/CPR/ 2013-07-01	10054006/CPR/ 2013-07-01	10054008/CPR/ 2013-07-01	10054010/CPR/ 2013-07-01	10054012/CPR/ 2013-07-01
	AVCP Systems	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	A1	A1	A1	A1	A1	A1
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	40	40	40	40	40	40
Wind, snow, permanent and imposed load resistance (mm)	4	4	5	6	8	10	12
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	30 (-2, -4)	30 (-1, -2)	31 (-1, -3)	32 (-1, -2)	34 (-2, -3)	35 (-2, -3)
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ coated side	3	0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	64	64	64	63	63	62
Light reflection coated/uncoated side $\rho_v, \rho_v'$	3	14 / 25	14 / 25	14 / 25	14 / 24	14 / 24	14 / 24
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	43	43	42	41	40	40
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	36 / 37	36 / 36	36 / 35	35 / 33	35 / 31	35 / 29
Solar factor	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	





## Declaration of Performance

### arcon sunbelt D60 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
 Flachglas-Veredlung GmbH & Co. KG  
 Werk Feuchtwangen  
 Industriestraße 10  
 D - 91555 Feuchtwangen

**arcon**  
 Flachglas-Veredlung GmbH & Co. KG  
 Werk Bucha  
 Gewerbegebiet "Am Amselberg" Schorba 4  
 D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

	LE/DoP-Nr.	40054100/CPR/ 2013-07-01	4005411/CPR/ 2013-07-01	40054110/CPR/ 2013-07-01	40054111/CPR/ 2013-07-01	40054120/CPR/ 2013-07-01	40054121/CPR/ 2013-07-01
	AVCP Systems	33.1	33.2	44.1	44.2	55.1	55.2
<b>Essential characteristics</b>							
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	NPD	NPD	NPD	NPD	NPD	NPD
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD	NPD	NPD	NPD	NPD
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ , coated side		0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	63	63	63	63	62	62
Light reflection coated/uncoated side $\rho_v, \rho_v'$		14 / 24	14 / 24	14 / 24	14 / 24	14 / 24	14 / 24
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	40	40	40	39	39	39
Solar reflection coated/uncoated side $\rho_e, \rho_e'$		35 / 31	35 / 30	35 / 30	35 / 29	35 / 29	35 / 28
Solar factor		NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
 This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D60 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

	LE/DoP-Nr.	40054130/CPR/ 2013-07-01	40054131/CPR/ 2013-07-01			
<b>Essential characteristics</b>	<b>AVCP Systems</b>	<b>66.1</b>	<b>66.2</b>			
<b>Safety in case of fire</b>						
Resistance to fire	1	NPD	NPD			
Reaction to fire	3.4	NPD	NPD			
External fire performance	3.4	NPD	NPD			
<b>Safety in use</b>						
Bullet resistance	1	NPD	NPD			
Explosion resistance	1	NPD	NPD			
Burglar resistance	3	NPD	NPD			
Pendulum body impact resistance	3	NPD	NPD			
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD			
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD			
<b>Protection against noise</b>						
Direct airborne sound reduction (db)	3	NPD	NPD			
<b>Thermal properties</b>						
U-value (W/m²K)	3	NPD	NPD			
Declared normal emissivity $\epsilon_n$ coated side		0.03	0.03			
<b>Radiation properties</b>						
Light transmission: $\tau_v$	3	62	62			
Light reflection coated/uncoated side $\rho_v, \rho_v'$		14 / 24	14 / 24			
<b>Solar energy characteristics</b>						
Solar transmission $\tau_e$		38	38			
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	35 / 27	35 / 26			
Solar factor		NPD	NPD			
<b>Durability</b>	3	PASS	PASS			

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D70 oHT



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

Essential characteristics	LE/DoP-Nr.	10056004/CPR/ 2013-07-01	10056005/CPR/ 2013-07-01	10056006/CPR/ 2013-07-01	10056008/CPR/ 2013-07-01	10056010/CPR/ 2013-07-01	10056012/CPR/ 2013-07-01
	AVCP Systems	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	A1	A1	A1	A1	A1	A1
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	40	40	40	40	40	40
Wind, snow, permanent and imposed load resistance (mm)	4	4	5	6	8	10	12
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	30 (-2, -4)	30 (-1, -2)	31 (-1, -3)	32 (-1, -2)	34 (-2, -3)	35 (-2, -3)
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ , coated side	3	0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	75	75	75	74	73	73
Light reflection coated/uncoated side $\rho_v, \rho_v'$	3	13 / 17	13 / 16	13 / 16	13 / 16	13 / 16	13 / 16
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	50	49	49	48	47	46
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	35 / 32	35 / 31	35 / 30	35 / 28	35 / 27	35 / 25
Solar factor	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D70 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Feuchtwangen  
Industriestraße 10  
D - 91555 Feuchtwangen

**arcon**  
Flachglas-Veredlung GmbH & Co. KG  
Werk Bucha  
Gewerbegebiet "Am Amselberg" Schorba 4  
D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)


#### EN 1096-4:2018

Essential characteristics	LE/DoP-Nr.	41056100/CPR/ 2013-07-01	41056101/CPR/ 2013-07-01	41056110/CPR/ 2013-07-01	41056111/CPR/ 2013-07-01	41056120/CPR/ 2013-07-01	41056121/CPR/ 2013-07-01
	AVCP Systems	33.1	33.2	44.1	44.2	55.1	55.2
<b>Safety in case of fire</b>							
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	3.4	NPD	NPD	NPD	NPD	NPD	NPD
External fire performance	3.4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Safety in use</b>							
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD	NPD	NPD	NPD	NPD
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD	NPD	NPD	NPD	NPD
<b>Protection against noise</b>							
Direct airborne sound reduction (db)	3	NPD	NPD	NPD	NPD	NPD	NPD
<b>Thermal properties</b>							
U-value (W/m²K)	3	NPD	NPD	NPD	NPD	NPD	NPD
Declared normal emissivity $\epsilon_n$ , coated side		0.03	0.03	0.03	0.03	0.03	0.03
<b>Radiation properties</b>							
Light transmission: $\tau_v$	3	74	74	74	74	73	73
Light reflection coated/uncoated side $\rho_v, \rho_v'$		13 / 16	13 / 16	13 / 16	13 / 16	13 / 16	13 / 16
<b>Solar energy characteristics</b>							
Solar transmission $\tau_e$	3	47	46	46	46	45	45
Solar reflection coated/uncoated side $\rho_e, \rho_e'$		35 / 27	35 / 26	35 / 26	35 / 25	35 / 24	35 / 23
Solar factor		NPD	NPD	NPD	NPD	NPD	NPD
<b>Durability</b>							
	3	PASS	PASS	PASS	PASS	PASS	PASS

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	



## Declaration of Performance

### arcon sunbelt D70 oHT (laminated safety glass)



**Coated glass, intended to be used in buildings and construction works**

**arcon**  
 Flachglas-Veredlung GmbH & Co. KG  
 Werk Feuchtwangen  
 Industriestraße 10  
 D - 91555 Feuchtwangen

**arcon**  
 Flachglas-Veredlung GmbH & Co. KG  
 Werk Bucha  
 Gewerbegebiet "Am Amselberg" Schorba 4  
 D - 07751 Bucha

[www.arcon-glas.de](http://www.arcon-glas.de)  
[info@arcon-glas.de](mailto:info@arcon-glas.de)

#### EN 1096-4:2018

	LE/DoP-Nr.	41056130/CPR/ 2013-07-01	41056131/CPR/ 2013-07-01			
<b>Essential characteristics</b>	<b>AVCP Systems</b>	<b>66.1</b>	<b>66.2</b>			
<b>Safety in case of fire</b>						
Resistance to fire	1	NPD	NPD			
Reaction to fire	3.4	NPD	NPD			
External fire performance	3.4	NPD	NPD			
<b>Safety in use</b>						
Bullet resistance	1	NPD	NPD			
Explosion resistance	1	NPD	NPD			
Burglar resistance	3	NPD	NPD			
Pendulum body impact resistance	3	NPD	NPD			
Resistance against sudden temperature changes and temperature differentials (K)	4	NPD	NPD			
Wind, snow, permanent and imposed load resistance (mm)	4	NPD	NPD			
<b>Protection against noise</b>						
Direct airborne sound reduction (db)	3	NPD	NPD			
<b>Thermal properties</b>						
U-value (W/m²K)	3	NPD	NPD			
Declared normal emissivity $\epsilon_n$ coated side		0.03	0.03			
<b>Radiation properties</b>						
Light transmission: $\tau_v$	3	73	73			
Light reflection coated/uncoated side $\rho_v, \rho_v'$		13 / 16	13 / 16			
<b>Solar energy characteristics</b>						
Solar transmission $\tau_e$		44	44			
Solar reflection coated/uncoated side $\rho_e, \rho_e'$	3	35 / 23	35 / 22			
Solar factor		NPD	NPD			
<b>Durability</b>	3	PASS	PASS			

NPD: No Performance Determined

The performance of the product identified is in conformity with the declared performance above.  
 This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Torsten Kunze Head Quality Management Coating Div.	Feuchtwangen, Bucha, 2021-01-01	